

Circlip Pliers

66HS

66HB

66SS

66SB



- Design of hidden spring
- Straight and angled pattern
- High strength of tip
- DIN 5254, DIN 5256



KT NO.	Tips	Overall length		Ø-tips	Capacity Ø mm		
		inch	mm				
66HS-07		7	188	1.8	19~60	176	8 / 48
66HB-07		7	175	1.8	19~60	176	8 / 48
66SS-07		7	188	1.8	19~60	195	8 / 48
66SB-07		7	175	1.8	19~60	195	8 / 48

67HS

67HB

67SS

67SB

68HS

68HB



68SS


68SB



- For internal retaining rings
- Straight and angled pattern
- DIN 5254, DIN 5256



- For external retaining rings
- Straight and angled pattern
- DIN 5254, DIN 5256



Japanese type

European type

Japanese type

European type



KT NO.	Tips	Overall length		Ø tips	Capacity Ø mm		
		inch	mm				
67HS-07		7	180	1.8	19~60	129	12 / 144
67HB-07		7	180	1.8	19~60	131	12 / 144
68HS-05		5	125	1.3	12~28	83	10 / 80
68HS-07		7	180	1.8	19~60	134	12 / 144
68HS-10		10	250	2.3	40~100	322	8 / 64
68HB-05		5	125	1.3	12~28	94	10 / 80
68HB-07		6-3/4	170	1.8	19~60	131	12 / 144
68HB-10		9-1/2	241	2.3	40~100	317	6 / 48

KT NO.	Tips	Overall length		Ø tips	Capacity Ø mm		
		inch	mm				
67SS-07		7	180	1.8	19~60	151	12 / 144
67SB-07		7	180	1.8	19~60	150	12 / 144
68SS-05		5	125	1.3	12~28	97	10 / 80
68SS-07		7	180	1.8	19~60	154	12 / 144
68SS-10		10	250	2.3	40~100	323	8 / 64
68SB-05		5	125	1.3	12~28	96	10 / 80
68SB-07		6-3/4	170	1.8	19~60	152	12 / 144
68SB-10		9-1/2	241	2.3	40~100	316	6 / 48



PLIERS