## Straight Pattern Snips

### 74410~74416

- Drop forged of finest quality steel induction hardened edges 60HRC
- Cuts straight flat face guides tool along straight line
- Blades individually hand edged for maximum cutting efficiency
- Cushion handle for comfort and better grip



KT NO.	Overall length mm	Cutting length mm	Copper (soft)	Cutting capo Cold-rolled Steel (soft)	acities (mm) Hard steel HRC 30 (Hard)	Stainless steel304	ŢġŢ	<del>6</del> / <del>6</del>
74410	254	51	0.94	0.78	0.60	0.45	480	6 / 36
74412	305	70	1.15	0.91	0.70	0.63	650	6 / 24
74414	356	76	1.41	1.20	1.00	0.70	780	6 / 24
74416	415	63	2.00	1.60	1.20	1.00	1700	3 / 12

# **Curved Tin Snips**

### 74512

74514

- Drop forged of finest quality steel induction hardened edges
  60HRC
- Double curved, hollow ground blades reduce friction for easier cutting
- British Gilbow type
- Cushion handle for comfort and better grip



74512 / 74514

	Overall	Cutting	Cutting capacities (mm)					
KT NO.	length mm	length mm	Copper (soft)	Cold-rolled steel (soft)	Hard steel HRC 30 (Hard)	Stainless steel304	₹ <u>a</u> ₹	8/8
74512	305	60	1.15	0.91	0.70	0.63	670	6 / 24
74514	356	65	1.40	1.20	1.00	0.70	920	6 / 24

# **Duckbill Pattern Snips**

### 74613

- Drop forged of finest quality steel induction hardened edges 60HRC
- Cuts moderately tight curves left, right or straight in light stock
- Blades individually hand edged for maximum cutting efficiency
- Cushion handle for comfort and better grip



	Overall	Cutting	Cutting capacities (mm)						
KT NO.	length mm	length mm	Copper (soft)	Cold-rolled steel (soft)	Hard steel HRC 30 (Hard)	Stainless steel304	₹ <u>a</u> Ť	8/8	
74613	330	72	1.20	0.84	0.61	0.61	720	6 / 24	

### Saw

### 7911-12

- Sliding metal bow
- Lightweight, resistant to oxidization and oil
- Two blade positions 45° and 90° including flush cut
- Ergonomic handle with hand stop
- Handle material: Zinc frame, soft grip TPR handle

KT NO.	Adjustable blade length (mm)	Overall length mm	ŢġŢ.	<u>8</u>  @
7911-12	300	400	628	6 / 36
7911-12P01	Blac	le	17	100 / 1200

