


Standard Socket

6330M

3/4"


▪ Metric-DIN 3124, ISO 2725-1



6330S

3/4"

▪ Inch-ANSI / ASME B107.1



KT NO.	mm	D1 mm	D2 mm	ℓ mm	L mm			
633017M	17	26.0	32.7	14	51	144	8	96
633019M	19	30.0	32.7	14	51	164	8	96
633021M	21	32.0	32.7	16	51	169	8	96
633022M	22	33.0	35.7	16	51	204	8	96
633023M	23	34.0	35.7	16	51	210	8	96
633024M	24	35.0	35.7	17	51	209	8	96
633026M	26	35.7	35.0	17	52	196	8	96
633027M	27	38.0	36.0	19	52	219	8	96
633028M	28	39.0	36.0	19	52	220	8	96
633029M	29	40.0	38.0	19	52	245	8	96
633030M	30	42.0	38.0	21	54	274	6	48
633032M	32	44.0	38.0	23	56	297	6	48
633033M	33	46.0	39.0	23	56	330	6	48
633034M	34	47.0	42.0	24	57	377	6	48
633035M	35	48.0	42.0	25	58	393	6	36
633036M	36	50.0	42.0	25	58	420	6	36
633038M	38	52.0	45.0	27	60	468	6	36
633041M	41	56.0	45.0	29	64	549	4	32
633042M	42	57.0	45.0	29	64	541	4	32
633046M	46	62.0	48.0	33	68	673	4	32
633048M	48	64.0	48.0	34	70	689	2	24
633050M	50	68.0	48.0	34	72	840	2	24
633054M	54	72.0	50.0	35	75	943	1	20
633055M	55	74.0	50.0	37	76	989	1	20
633058M	58	77.0	50.0	37	78	1044	1	20
633060M	60	80.0	50.0	40	78	1072	1	20
633063M	63	83.0	55.0	40	81	1201	1	12
633065M	65	85.0	58.0	43	83	1311	1	12
633070M	70	92.0	58.0	46	88	1634	1	12

KT NO.	inch	D1 mm	D2 mm	ℓ mm	L mm			
633022S	11/16	26	35.7	14	50.8	144	8	96
633024S	3/4	30	35.7	14	50.8	164	8	96
633026S	13/16	32	35.7	16	50.8	169	8	96
633028S	7/8	33	35.7	16	51.0	206	8	96
633030S	15/16	35	35.7	17	51.0	213	8	96
633032S	1	35	35.7	17	52.0	208	8	96
633034S	1-1/16	38	36.0	19	52.0	219	8	96
633036S	1-1/8	40	38.0	19	52.0	244	8	96
633038S	1-3/16	42	38.0	21	54.0	273	6	48
633040S	1-1/4	44	38.0	23	56.0	299	6	48
633042S	1-5/16	46	39.0	23	56.0	331	6	48
633044S	1-3/8	48	42.0	25	58.0	393	6	36
633046S	1-7/16	50	42.0	25	58.0	412	6	36
633048S	1-1/2	52	45.0	27	60.0	477	6	36
633050S	1-9/16	54	45.0	28	62.0	493	4	32
633052S	1-5/8	56	45.0	29	64.0	564	4	32
633054S	1-11/16	58	45.0	29	65.0	562	4	32
633056S	1-3/4	60	48.0	31	66.0	636	4	32
633058S	1-13/16	62	48.0	34	68.0	669	4	32
633060S	1-7/8	64	48.0	34	70.0	712	2	24
633062S	1-15/16	66	48.0	34	70.0	768	2	24
633064S	2	68	48.0	34	72.0	826	2	24
633066S	2-1/16	70	50.0	35	74.0	893	1	20
633068S	2-1/8	72	50.0	35	75.0	944	1	20
633070S	2-3/16	74	50.0	37	76.0	957	1	20
633072S	2-1/4	76	50.0	37	76.0	962	1	20
633074S	2-5/16	78	50.0	37	78.0	1084	1	20
633076S	2-3/8	80	50.0	40	78.0	1093	1	20
633078S	2-7/16	82	55.0	40	81.0	1160	1	12
633080S	2-1/2	84	55.0	40	81.0	1238	1	12
633082S	2-9/16	85	58.0	43	83.0	1355	1	12
633084S	2-5/8	86	58.0	43	83.0	1277	1	12
633086S	2-11/16	90	58.0	43	85.0	1514	1	12
633088S	2-3/4	92	58.0	46	88.0	1642	1	12

